

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/059922 A1

(51) International Patent Classification⁷: **G11C 14/00**

(21) International Application Number:
PCT/EP2004/014104

(22) International Filing Date:
10 December 2004 (10.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03028758.5 12 December 2003 (12.12.2003) EP

(61) Related by addition to earlier application or grant:
DE PCT/EP04/14104 (POA)
Filed on 10 December 2004 (10.12.2004)

(71) Applicant (for all designated States except US): **X-FAB SEMICONDUCTOR FOUNDRIES AG** [DE/DE]; Haarbergstrasse 67, 99097 Erfurt (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **IVANOV, Valeri Dimitrov** [BG/DE]; c/o, X-FAB SEMICONDUCTOR

FOUNDRIES AG, Haarbergstrasse 67, 99097 Erfurt (DE). **LIEBING, Hartmut** [DE/DE]; Niels-Bohr-Weg 12, 99097 Erfurt (DE).


(74) Agents: **LEONHARD OLGEMOELLER FRICKE** et al.; Postfach 10 09 62, 80083 Muenchen (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE (patent), DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **NON-VOLATILE SEMICONDUCTOR LATCH USING HOT-ELECTRON INJECTION DEVICES**



(57) Abstract: The invention concerns semiconductor latches capable of memorizing any programmed information even after power supply has been removed. Used is a 0.6 m BiCMOS EPROM process but it is applicable in any other process having hot electron injection devices like EPROM, Flash EEPROM. Suggested is a bi-stable latch circuit having a pair of cross-coupled branches (I,II), each branch including a complementary driver and a load connected between a drain line and a source line and a non-volatile memory cell having a program transistor and a read transistor, at least one of said drivers and loads including said read transistor, said driver and load of said branch connected in series at a respective output node, said read transistor and program transistor having a common floating gate and separate control gates, said control gate of said program transistor connected to a program voltage, the drain of said program transistor connected to a respective input node, said control gate of said read transistor in said branch connected to said output node of the other branch (II).

WO 2005/059922 A1



Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.